



TELECRANE®

禹鼎電子股份有限公司

F25 工 · 業 · 用 · 無 · 線 · 電 · 遙 · 控 · 器



安全 - 可靠 - 容易操作

- 符合歐洲 EN ISO 13849-1 安全標準 (急停達等級 4 · 操作達等級 3)
- 簡捷輕巧外型，配合堅固耐用之外殼，易於操作。
- 模組化雙 CPU、雙安全繼電器設計，品質更加可靠穩定。
- 可經由 PC 軟體設定多種按鍵功能，滿足您各種操作需求。
- 接收機含輸出電纜線，安裝簡單 · 快速。
- 接收機內建警報器，不須額外加裝其它警示器
- 具遙控配對之功能，可立即執行現場維修。



TELECRANE®

www.telecranetw.com.tw

**F25 系列
接收機**



F25-6S/6D

- 6個單速 / 雙速按鍵
- 1個急停按鍵
- 1個啓動按鍵
- 1個旋轉式鑰匙
- 1個警報按鍵

F25-8S/8D

- 8個單速 / 雙速按鍵
- 1個急停按鍵
- 1個啓動按鍵
- 1個旋轉式鑰匙
- 1個警報按鍵

F25-10S/10D

- 10個單速 / 雙速按鍵
- 1個急停按鍵
- 1個啓動按鍵
- 1個旋轉式鑰匙
- 1個警報按鍵



週邊配件



- 軟體光碟
- USB導線組



· 被動式天線



· 拷貝機



· 發射機護套

產品規格

一般

操作頻率	70個頻道
漢明碼	≥ 4
操作距離	可達100公尺
操作溫度	-40 °C ~ +85 °C
識別碼	超過100萬組(工廠設定, 永不重複)

發射機

電 源	四顆 1.5 V 電池 (AA 電池)
射頻功率	< 10 mW
電源控制	三段式 LED 燈顯示
尺 寸	186 x 61 x 51 mm (長 x 寬 x 高)
重 量	大約 265g (包含電池)

接收機

電 源	24 / 48 / 110 / 220 / 380VAC (50/60Hz), ±20%
尺 寸	200 x 162 x 107 mm (長 x 寬 x 高)
重 量	大約1550g (不含電纜)



F25 工 · 業 · 用 · 無 · 線 · 電 · 遙 · 控 · 器

禹鼎電子股份有限公司

TELECRANE 台灣授權總經銷
 Email: info@telecranetw.com.tw
 Tel: 06-233-9484
 Fax: 06-233-9485

TELECRANE®

www.telecranetw.com.tw

2008.01

Safe / Reliable / Easy to Use



F25-6S/6D



F25-8S/8D



F25-10S/10D

F25-6S/6D model

Weight About 265 g (w/Batteries)
Dimension 156 x 61 x 51 mm (L x W x H)

F25-8S/8D & F25-10S/10D models

Weight About 320 g (w/Batteries)
Dimension 186 x 61 x 51 mm (L x W x H)

Transmitter Unit

- 6 ~ 10 Single / double steps pushbuttons
- Start pushbutton
- Rotary key switch + Emergency stop pushbutton
- Alarm pushbutton (6S/6D Model activated by start pushbutton)

Main Features

Safety Function of "STOP" & "CONTROL"

In accordance with EN ISO 13849-1 Cat. 4

Windows Software

Programmable function setting through PC.

Remote Pairing Technology

To allow instant maintenance on site

Enclosure Durability (Harsh Environment)

Nylon-Fiber made housing for extra shock resistant.

Built-in Alarm System

No need to install extra warning devices

Pre-Wiring Receiver

Receiver pre-installed wire made the installation easy and fast ever.

TELECRANE TAIWAN

Email: info@telecranetw.com.tw

Tel: 06-233-9484

Fax: 06-233-9485



Receiver Unit

Weight About 1550 g (w/o cable)
Dimension 200 x 162 x 107 mm (L x W x H)

General Spec.

	Operation Frequency	433.05 ~434.79 MHz
	Hamming Distance	≥ 4
	Operation Range	Up to 100 Meters
	Temperature Range	-40°C ~ +85°C
	ID CODE	Over 4.3 billion unique ID code available
Transmitter	Power Supply	4 AA size battery, Alkaline / Rechargeable (NiMH)
	Emission Power	< 10mW
	Power Indication	3-stage with LED indication
Receiver	Power Supply	24 / 48/ 110 / 220 / 380 VAC (50 / 60Hz) ±20%, 12/24 VDC
	Alarm	Built-in horn inside the receiver

ACCESSORIES



Copier



Passive Antenna



TX Protective Case



Battery Charger

TELECRANE TAIWAN

Email: info@telecranetw.com.tw

Tel: 06-233-9484

Fax: 06-233-9485